



Call 1-800-568-5657 to order today!

Introducing the fastest shipping times from Acco® on Wire Rope Hoists. Now you can order stocked configurations of Wright® Speedway® and Work-Rated® Wire Rope Hoists with same day shipping.

Modify your hoist and you'll still receive same day or next day shipping depending on the modifications selected. Call us, many times we can ship the same day!

SPEEDWAY®

Rapid ship wire rope hoists available from **1 to 5 Tons.**



WORK-RATED

Rapid ship wire rope hoists available from **5 to 20 Tons.**



Same day or next day shipping

Place your order for stocked configurations before 2 pm Eastern Standard Time and we'll ship your hoist the same day. Choose **voltage** or **flange width adjustments** and we'll ship your hoist next day.

All stocked configurations include these standard features:

- Mechanical Load Brake Double Reeving Domestic Motors With Thermostats Steel Sheaves Dual Tread Trolley Wheels
- NEMA 3R Enclosure Upper and Lower Geared Limit Switch Gravity Upper Limit Switch Branch Circuit Fusing
- Overload Cut-Off Device (optional on Speedway® hoists)

=48 to 72 hour shipping

Choose from the modifications below and we'll ship your hoist within 48-72 hours.

48 to 72 hour modifications include:

- VFD Trolley Motion (2-Speed or 2-Step INF VAR)
- 1T Speedway® VFD Hoist Motion (2-Speed or 2-Step INF VAR)
- 2T Speedway® VFD Hoist Motion (2-Speed or 2-Step INF VAR)
- 3T Speedway® VFD Hoist Motion (2-Speed or 2-Step INF VAR)
- 5T Speedway® VFD Hoist Motion (2-Speed or 2-Step INF VAR)
- 5T Work-Rated® VFD Hoist Motion (2-Speed or 2-Step INF VAR)
- 10T Work-Rated® VFD Hoist Motion (2-Speed or 2-Step INF VAR)
- Flat Tread Wheels
- Overload Cut-Off Device for Speedway® Hoists
- Mainline Contactor
- 2-Motion Radio (includes warning horn and quick disconnect plug)
- 3-Motion Radio (includes warning horn and quick disconnect plug)
- Pendant Cord and Strain Chain length (8 or 14 conductors)

Other modifications available:

- 5T, 10T and 20T Work-Rated® Deck Hoist Controls
- Drop Down Lugs
- Rubber Bumpers

- Trolley Brake
- Thermal Overload Relays
- 10-5/8" to 14" Flange Width



SPECILIAY Wire Rope Hoists stocked configurations

Speedway® Hoists are stocked with single speed controls for hoist and trolley motions. Inverters can be added as optional equipment. Hoists feature Weston style mechanical load brake, AC hoist motor brake, US manufactured motors, double reeving for true vertical lift, gravity type upper limit switch, geared upper and lower limit switch, branch circuit fuses, steel sheaves and dual tread trolley wheels. Hoists have NEMA 3R enclosure and are for 208/230/460-3-60 power supplies.

MODEL NUMBER	STOCK NUMBER	CAP. (TONS)	LIFT (FT.)	LIFT SPEED (FPM)	MOUNTING ARRANGEMENT	TROLLEY SPEED (FPM)	TROLLEY FLANGE	REEVING	HMI DUTY
C1W01D025-15M2D1	3181070	1T	25′	15	MTZD. TROLLEY	50	3 1/4" - 10 1/2"	2-PD	H4
C1W02D025-15M2D1	3181060	2T	25′	15	MTZD. TROLLEY	50	3 1/4" - 10 1/2"	2-PD	H4
C1W03D021-15M2D1	3181020	3T	21′	15	MTZD. TROLLEY	50	3 1/4" - 10 1/2"	2-PD	H4
C1W05D019-12M4D1	3181050	5T	19' - 6"	12	MTZD. TROLLEY	50	3 1/4" - 10 1/2"	4-PD	H4

WORK-Rateo Wire Rope Hoists stocked configurations

Work-Rated® Hoists are stocked with single speed controls for hoist and trolley motions (excluding deck mount). Inverters can be added as optional equipment. Hoists feature Weston style mechanical load brake, overload cut-off device, DC hoist motor brake, US manufactured motors, double reeving for true vertical lift, gravity type upper limit switch, geared upper and lower limit switch, branch circuit fuses, steel sheaves and dual tread trolley wheels. Hoists have NEMA 3R enclosure and are for 230/460-3-60 power supplies.

MODEL	STOCK	CAP.	LIFT	LIFT	MOUNTING	TROLLEY	TROLLEY	REEVING	НМІ
NUMBER	NUMBER	(TONS)	(FT.)	SPEED	ARRANGEMENT	SPEED	FLANGE		DUTY
				(FPM)		(FPM)			
C2W05D020-15M2D1	3284070	5T	20′	15	MTZD. TROLLEY	50	3 1/4" - 10 1/2"	2-PD	H4
C2W05D036-15M2D1	3285180	5T	36′	15	MTZD. TROLLEY	50	3 1/4" - 10 1/2"	2-PD	H4
C3W10D036-15M4D1	3385190	10T	36′	15	MTZD. TROLLEY	50	4 1/2" - 10 1/2"	4-PD	H4
C2W05D036-15D2D0*	3284200	5T	36′	15	DECK MOUNT	NA	NA	2-PD	H4
C3W10D036-15D4D0*	3386190	10T	36′	15	DECK MOUNT	NA	NA	4-PD	H4
C5W20D039-15D4D0*	3580010	20T	39′	15	DECK MOUNT	NA	NA	4-PD	H4

^{*} Less control

Don't see what you are looking for? Call Acco to customize your Wire Rope Hoist.

Ask about Acco's selection of Electric Chain Hoists and

Crane Kits available for rapid shipment.





76 Acco Drive, Box 792, York, PA 17405-0792 717-741-4863, 800-967-7333, FAX 800-715-8897

E-mail: info@accomhs.com

www.accomhs.com